

Solar Guard Paint



In countries with high light intensities, the temperature of plastic film may increase significantly on surfaces where it comes into contact with the metal structure, causing the plastic film to wear prematurely. SolarGuard allows you to prevent wear effectively. It contains a microscopically divided pigment that reflects solar radiation.

Advantages of SolarGuard:

- Excellent coverage and great reflective power
- Extremely UV-stable and therefore highly resistant to wear
- Creates a flexible film
- Water-based product
- Will not affect the quality of plastic film
- Safe for humans, animals and for the environment

How to use it?

Apply SolarGuard undiluted in narrow bands to the plastic film or to the metal structure.

One 16 litre bucket is sufficient for 250 to 300 square metres or for a band with a length of 2,500 to 3,000 metres and a width of 10 cm.

Product Detail

Agriplast Tech India Private Limited

Brand	Mardenkaro
Shape	Liquid
Color	White
Minimum Order Quantity	1 Bucket

Survey No. 426/ 3B-1B, Nallur Village, Opp Nallur Government High School,
 Panchayat Union & Taluk, Krishnagiri Dist - 635 103, Tamil Nadu, INDIA
 Customer Care : +91-81414 46666 | E-mail : support@agriplast.co.in | Website : www.agriplast.co.in
 CIN : U01403KA2011PTC057924



Bucket	16 litres
Port of Dispatch	Ex Hosur
Delivery Time	immediate
Packaging Details	Bucket of 16 litres